



TECHNICAL SPECIFICATION

Supply and installation of supports for raised floors "STAR.T".

The supports are composed of two polypropylene elements with a diameter of 152mm and with an adjustable height from 10mm up to 15mm, in the upper part there are N°4 spacer tabs with a thickness of either 2, 3, or 4mm and a height of 12mm.

In the base there are holes for the outflow of water. There are housings for various accessories and a hole for the adjustment key.

By using the special STAR.T extension, it is possible to reach a maximum height of 30mm.

CHARACTERISTICS:

- Minimum height 8mm with only upper body used
- Minimum height with also using the base 10mm
- Height adjustable up to 15mm
- Prepared for use with extensions having a height of 5mm
- Holes for water drainage
- Hole for inserting adjustment wrench
- N°4 spacer flaps height 12mm thickness 2-3-4mm
- fracturable and removable

RAW MATERIAL:

Polypropylene

ENVIRONMENTAL IMPACT:

recyclable material - not dangerous

APPLICATIONS SURFACES:

- On any waterproofing membrane
- On any insulating hard panel
- On any compact and solid surface

APPLICATIONS AREA:

Can be used with any prefabricated self supporting element for outdoor flooring

GENERAL CHARACTERISTICS & PROPERTIES

	UNIT	VALUE	TOLERANCE +/-
BASE DIAMETER	mm	152	+/- 1.0
BASE THICKNESS	mm	2	+/- 0.2
SURFACE OF THE BASE	cmq	182	+/- 5
TABS THICKNESS	mm	2-3-4	+/- 0.2
TABS HEIGHT	mm	12	+/- 0.2
SHORE	Shore d	70	+/- 3



TECHNICAL DATA SHEET

PEDESTAL STAR.T

ITEMS CHARACTERISTICS & PROPERTIES

STAR.T_E003010015	UNIT	VALUE	TOLERANCE	PACK/STORAGE	
min HEIGHT	mm	10	+/- 1,0	PIECES PER KIT	20
MAX HEIGHT	mm	15	+/- 1,0	PIECES PER BOX	100
WEIGHT	kg	0.091	+/- 5 %	BOXES PER PALLET	54
MAX CENTRAL COMPRESSION RESISTANCE*	kN	35.53	/	BOX DIMENSION	40x40x24cm
				BOX WEIGHT	9.4kg
				PALLET	80x120cm
				PCS PER PALLET	5400

The code refers to the model with 4 mm thick fins, 2 and 3 mm fins available on request

*Tests made by Civil and Environmental Department of University of Padova. 1 kN = 102 kg

The packaging of the supports consists of cardboard boxes. The final packaging of the pallets is made with the wrapping of a polyethylene film. Indoor storage, protected from precipitation, is recommended.

INSTALLATION METHOD: The product is laid dry, without the need for adhesives or other types of fixings.

The above data are relevant to current production and may be changed or updated by Eterno Ivica at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Eterno Ivica. All rights reserved.